

Datasheet for: 103259


Safety ball valve not lockable, Venting hole, Rp 1 1/2

Safety ball valve not lockable with venting hole, nickel-plated brass, Operating temp. max. 60°C, Rp 1 1/2, DN 40, PN max. 12 bar . Brass safety ball valves. Specially designed for pneumatic applications. The ball valve shuts off the supply side and relieves the application into the atmosphere.

Type number	350.507
Article number	103259
EAN/barcode	 4047322076449
Your price	86,89 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	150.0 mm
B	104.0 mm
Ball	Nickel-plated brass
DN	40.0
Hand lever	Die-cast aluminium, black
Housing	Nickel-plated brass
L	114.0 mm
Max. operating pressure	12 bar
Max. operating temperature	60 °C
Page No.	HK281
Page No. SF	SF044
Sealant	PTFE
Standard thread	Rp thread acc. to ISO 7-1
Stem	Nickel-plated brass
Stuffing box	Nickel-plated brass
Thread	Rp 1 1/2
Thread material	Brass with a bare metal surface

Variants

Article number	Thread	DN	Price
103259	Rp 1 1/2	40.0	86,89 € / Stk
103253	Rp 1/4	8.0	18,29 € / Stk
103254	Rp 3/8	10.0	18,29 € / Stk
103255	Rp 1/2	15.0	19,45 € / Stk
103256	Rp 3/4	20.0	30,87 € / Stk
103257	Rp 1	25.0	38,56 € / Stk
103258	Rp 1 1/4	32.0	62,79 € / Stk
103260	Rp 2	50.0	133,37 € / Stk

More Pictures

