

Datasheet for: 116596



2/2-way solenoid valve »2KS« NO, directly operated, 230 V, 50 Hz

2/2-way solenoid valve »2KS«, Stainless steel, NO, directly operated, 230 V, 50 Hz, Medium temp. max 80°C/90°C, G 3/8, PN 0-20 bar . Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MVH 1523 ES
-------------	-------------

Article number	116596
----------------	--------

EAN/barcode	
-------------	--



4047322324014

Your price	87,18 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	85.0 mm
B	52.0 mm
C	92.0 mm
DN	3
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. operating pressure	20 bar
Page No.	HK330
Page No. AS	AS050
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 3/8
Type	2
Valve seat	Stainless steel 1.4301

Variants

<i>Article number</i>	<i>Thread</i>	<i>DN</i>	<i>Price</i>
116596	G 3/8	3	87,18 € / Stk
116594	G 1/4	1.5	62,28 € / Stk
116592	G 1/8	1.5	62,28 € / Stk
116598	G 1/2	3	87,18 € / Stk

More Pictures

