

Datasheet for: 100682



Filter »variobloc« with PC container, Size 2, G 1

Filter »variobloc«, PC container, Size 2, G 1, Input pressure max. 16 bar, Med. / ambient temp. max. 50 °C, Manual bleeder valve . Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles). Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VF 26
Article number	100682
EAN/barcode	 4047322212694
Your price	87,48 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	124.0 mm
B	202.0 mm
Bowl	Polycarbonate container
C	26.0 mm
Condensate drain	Manual
Filter rating	40.0 µm
Flow rate	3500 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK105
Sealant	NBR
Series	variobloc
Size	2
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
100682	G 1	3500 l/min	2	87,48 € / Stk
100678	G 1/4	1800 l/min	1	32,88 € / Stk
100679	G 3/8	2000 l/min	1	32,88 € / Stk
100680	G 1/2	3200 l/min	2	52,60 € / Stk
100681	G 3/4	3500 l/min	2	52,60 € / Stk

More Pictures

