

Datasheet for: 125331



Active charcoal filter »variobloc« Metal container, Size 1, G 3/8

Active charcoal filter »variobloc« with metal container incl. viewing tube, 0.003 mg/m³, Size 1, G 3/8, Input pressure max. 20 bar . Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Type number	VAK 23 M
Article number	125331
EAN/barcode	 4047322397728
Your price	116,43 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	48.0 mm
Air quality acc. to ISO 8573.1	Class 1 dirt, class 1 oil
B	142.0 mm
Bowl	Metal container with viewing tube
C	22.0 mm
Flow rate	1000 l/min
Flow rate measurement	At P ₁ = 7 bar and pressure drop Δp = 0,1 bar
Max. ambient temperature	80 °C
Max. input pressure	20 bar
Max. medium temperature	50 °C
Page No.	WEB
Residual oil content	0.003 mg/m ³
Series	variobloc
Size	1
Thread	G 3/8

Variants

Article number	Thread	Flow rate	Size	Price
125331	G 3/8	1000 l/min	1	116,43 € / Stk
125334	G 1	1300 l/min	2	203,46 € / Stk
125333	G 3/4	1300 l/min	2	164,41 € / Stk
125330	G 1/4	800 l/min	1	116,43 € / Stk
125332	G 1/2	1200 l/min	2	164,41 € / Stk

More Pictures

