


## Datasheet for: 106600


**5/2-way valve, Single-sided pneumatic, monostable, G 1/4, DN 7.5**

5/2-way valve, Single-sided pneumatic, monostable, G 1/4, DN 7.5, Operating pre. 2.5 to 10 bar, Operating temp. -10 °C to 60 °C . This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems. Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

Type number	517.622
Article number	106600
EAN/barcode	 4047322278645
Your price	87,94 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/4
DN	7.5
Electrical connection	Coupler plug PG 9, form B
Flow rate 1	1500 NI/min
Flow rate measurement 1	Flow rate at 6 bar and $\Delta p$ 1.0 bar
Function	5/2
Housing	Anodised aluminium, blue
Manual control	non-latching
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. pilot pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Monostable
Page No.	HK473
Protection IP	IP 65 (DIN 46244)
Sealant	NBR
Spool	Stainless steel

Symbol

27

**Variants**

<i>Article number</i>	<i>Connection</i>	<i>DN</i>	<i>Flow rate 1</i>	<i>Price</i>
106600	G 1/4	7.5	1500 NI/min	87,94 € / Stk
106601	G 1/2	15.0	4600 NI/min	276,97 € / Stk

**More Pictures**
