


Datasheet for: 137361



Blocking valve pneumat. actuated, single-acting NO, FKM, Rp 1/2

Blocking valve pneumat. actuated, single-acting, NO, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 4.2-8 bar, Rp 1/2 . 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

Type number	351.982
Article number	137361
EAN/barcode	 4047322513449
Your price	118,48 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	NAMUR interface, direct: 2 x G 1/8
DN	15.0
H	51.7 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
L	112.0 mm
Max. operating pressure	10 bar
Max. operating temperature	150 °C
Max. pilot pressure	8.0 bar
Min. operating temperature	-20 °C
Min. pilot pressure	4.2 bar
Mounting position	Any
Page No.	HK346
Sealant	FKM
Spring	Stainless steel
Thread	Rp 1/2
Version	single-acting - spring to open

Variants

Article number	Thread	DN	Price
137361	Rp 1/2	15.0	118,48 € / Stk
137365	Rp 1 1/2	40.0	286,78 € / Stk
137366	Rp 2	50.0	392,65 € / Stk
137362	Rp 3/4	20.0	141,23 € / Stk
137360	Rp 3/8	10.0	108,43 € / Stk
137364	Rp 1 1/4	32.0	229,26 € / Stk
137363	Rp 1	25.0	164,25 € / Stk

More Pictures

