


Datasheet for: 116553


2/2-way solenoid valve »2W« NC, pilot operated, 230 V, 50 Hz

2/2-way solenoid valve »2W«, Brass, NC, pilot operated, 230 V, 50 Hz, Medium temperature max. 80 °C/90 °C, G 3/4, PN 0.5 - 10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1542
Article number	116553
EAN/barcode	 4047322325066
Your price	89,05 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	82.0 mm
C	115.4 mm
DN	20
Housing	Brass
Internal parts	Stainless steel
Max. operating pressure	10 bar
Min. operating pressure	0.5 bar
Page No.	HK326
Page No. AS	AS047
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 3/4
Type	3
Valve seat	Brass

Variants

Article number	Thread	DN	Price
116553	G 3/4	20	89,05 € / Stk
116551	G 1/2	15	73,55 € / Stk
116555	G 1	25	102,22 € / Stk

More Pictures

