


Datasheet for: 107577


End distributor socket, G1/2, 3 safety coupl. I.D. 7.4, max.15bar

End distributor socket, with 3 safety couplings I.D. 7.4, input G 1/2, Operat. pressure max. 15bar, Ambient temp. -10°C to 50°C. 2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. Available with 2 or 3 pre-assembled, pushbutton-type safety couplings and 2 inlet thread sizes for input and output threads (Not combinable). All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

Type number	EVDS12-3
Article number	107577
EAN/barcode	 4047322401784
Your price	100,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Coupling	3 x Safety coupling
Height	59.0 mm
Housing	Glass fibre-reinforced plastic PA6 GF 30
Inlet thread	G 1/2
Max. operating pressure	12 bar
Max. temperature range	50 °C
Max. tightening torque brass thread	12 Nm
Max. tightening torque mounting holes	4 Nm
Min. temperature range	-10 °C
Page No.	HK579
Page No. SK	SK063
Page No. TS	TS010
Thread material	Brass

Width 156.0 mm

Variants

<i>Article number</i>	<i>Inlet thread</i>	<i>Coupling</i>	<i>Price</i>
107577	G 1/2	3 x Safety coupling	100,71 € / Stk
107579	G 3/4	3 x Safety coupling	119,88 € / Stk
107576	G 1/2	2 x Safety coupling	71,71 € / Stk
107578	G 3/4	2 x Safety coupling	91,82 € / Stk

More Pictures

