


## Datasheet for: 116159


**5/3-way valve, electropneumatic, »4V« Centre closed, 230 V, 50 Hz**

5/3-way valve, electropneumatic, »4V«, Centre closed, G 1/8, 230 V, 50 Hz, Operating pressure 1.5-8 bar, Temp. -20°C to 70°C . 5/3-way pilot valves - Electro-pneumatic -

Type number	517.3101
Article number	116159
EAN/barcode	 4047322310840
Your price	101,14 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	400 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Mid-position closed
Page No.	HK469
Page No. AS	AS088
Protection IP	IP 65
Size	100
Symbol	37
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

## Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116159	G 1/8	G 1/8	230 V, 50 Hz	400 l/min	100	101,14 € / Stk
116164	G 1/2	G 1/2	230 V, 50 Hz	1600 l/min	400	158,29 € / Stk
116154	G 1/4	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116153	G 1/8	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116151	M5	M5	24 V DC	250 l/min	100	101,14 € / Stk
116163	G 3/8	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116156	G 3/8	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116155	G 1/4	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116152	G 1/8	G 1/8	24 V DC	400 l/min	100	101,14 € / Stk
116157	G 1/2	G 1/2	24 V DC	1600 l/min	400	158,29 € / Stk
116158	M5	M5	230 V, 50 Hz	250 l/min	100	101,14 € / Stk
116160	G 1/8	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116161	G 1/4	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116162	G 1/4	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk

## More Pictures

