

Datasheet for: 116173


5/3-way valve, electropneumatic, »4V« Centre vented, 230 V, 50 Hz

5/3-way valve, electropneumatic, »4V«, Centre vented, G 1/8, 230 V, 50 Hz, Operating pressure 1.5-8 bar, Temp. -20 °C to 70 °C . 5/3-way pilot valves - Electro-pneumatic -

Type number	517.3301
Article number	116173
EAN/barcode	 4047322310994
Your price	101,14 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	400 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Mid-position exhausted
Page No.	HK469
Page No. AS	AS088
Protection IP	IP 65
Size	100
Symbol	38
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116173	G 1/8	G 1/8	230 V, 50 Hz	400 l/min	100	101,14 € / Stk
116165	M5	M5	24 V DC	250 l/min	100	101,14 € / Stk
116168	G 1/4	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116172	M5	M5	230 V, 50 Hz	250 l/min	100	101,14 € / Stk
116171	G 1/2	G 1/2	24 V DC	1600 l/min	400	158,29 € / Stk
116170	G 3/8	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116169	G 1/4	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116177	G 3/8	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116178	G 1/2	G 1/2	230 V, 50 Hz	1600 l/min	400	158,29 € / Stk
116175	G 1/4	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116174	G 1/8	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116176	G 1/4	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116167	G 1/8	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116166	G 1/8	G 1/8	24 V DC	400 l/min	100	101,14 € / Stk

More Pictures

