


Datasheet for: 125319


Filter »variobloc« with metal container, Size 2, G 1

Filter »variobloc« with metal container incl. viewing tube, Size 2, G 1, Input pressure max. 20 bar, Manual bleeder valve. Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles). Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VF 26 M
Article number	125319
EAN/barcode	 4047322212700
Your price	121,04 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	124.0 mm
B	202.0 mm
Bowl	Metal container with viewing tube
C	26.0 mm
Condensate drain	Manual
Filter rating	40.0 μm
Flow rate	3500 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	80 °C
Max. input pressure	20 bar
Max. medium temperature	50 °C
Page No.	WEB
Sealant	NBR
Series	variobloc
Size	2
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
125319	G 1	3500 l/min	2	121,04 € / Stk
125315	G 1/4	1800 l/min	1	60,11 € / Stk
125316	G 3/8	2000 l/min	1	60,11 € / Stk
125317	G 1/2	3200 l/min	2	85,73 € / Stk
125318	G 3/4	3500 l/min	2	85,86 € / Stk

More Pictures

