


## Datasheet for: 156211

**Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Hose 5x3**


Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Hose connection 5x3, Operating pressure - 35 bar, Temp. -20°C to 200°C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.08/8-ES-E
Article number	156211
EAN/barcode	 4047322625159
Your price	90,14 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel 1.4034
Connection	Hose connection 5x3
DN	2.7
Flow rate	120 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel 1.4305
Length	33.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK521
Retaining ring	Stainless steel 1.4310
Sealant	FPM
Sleeve	Stainless steel 1.4305

Spring  
Valve body  
a/f

Stainless steel 1.4310  
Stainless steel 1.4305  
9 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
156211	Hose connection 5x3	90,14 € / Stk
156210	Hose connection 4x3	90,14 € / Stk
156212	Hose connection 6x4	90,14 € / Stk

## More Pictures

