


Datasheet for: 156212

Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Hose 6x4


Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Hose connection 6x4, Operating pressure - 35 bar, Temp. -20°C to 200°C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.08/9-ES-E
Article number	156212
EAN/barcode	 4047322625142
Your price	90,14 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel 1.4034
Connection	Hose connection 6x4
DN	2.7
Flow rate	120 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 1$ bar
Housing	Stainless steel 1.4305
Length	33.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK521
Retaining ring	Stainless steel 1.4310
Sealant	FPM
Sleeve	Stainless steel 1.4305

Spring
Valve body
a/f

Stainless steel 1.4310
Stainless steel 1.4305
9 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
156212	Hose connection 6x4	90,14 € / Stk
156211	Hose connection 5x3	90,14 € / Stk
156210	Hose connection 4x3	90,14 € / Stk

More Pictures

