

Datasheet for: 139590


3/2-way valve »FUTURA«, electr. actuated, 115 V AC, Size 2, G 3/8

3/2-way valve »FUTURA«, electr. actuated with solenoid 115 V AC, 50 Hz, Size 2, G 3/8, Exhaust G 1/2, Input pressure 2 - 10 bar . Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FU 967-115V
-------------	-------------

Article number	139590
----------------	--------

EAN/barcode	 4047322535083
-------------	--



Your price	101,62 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	63.0 mm
B	150.3 mm
C	93.8 mm
Connecting thread	Material: Die-cast zinc
Duty cycle	100 %
Electrical connection	Socket coupling EN 175301-803, form C, poles 2+PE
Exhaust air	G 1/2
Flow rate	4500 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ_p = 1 bar
Holding power with 50 Hz AC voltage	1.6 VA
Housing	PA66 GF60
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	2.0 bar
Min. temperature range	-10 °C
Page No.	HK055

Pick-up power with 50 Hz AC voltage	2.2 VA
Power input	2.5 Watt with DC voltage
Protection IP	IP 65
Series	FUTURA
Size	2
Thread	G 3/8

Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
139590	G 3/8	G 1/2	4500 l/min	2	101,62 € / Stk
139591	G 1/2	G 1/2	4500 l/min	2	101,62 € / Stk
156614	G 3/4	G 1/2	12500 l/min	4	210,98 € / Stk
156615	G 1	G 1/2	12500 l/min	4	210,98 € / Stk
156612	G 1/4	G 1/4	2000 l/min	1	95,39 € / Stk
156613	G 3/8	G 1/4	2000 l/min	1	95,39 € / Stk

More Pictures

