

Datasheet for: 116564



2/2-way solenoid valve »2KS« NO, pilot operated, 230 V, 50 Hz

2/2-way solenoid valve »2KS«, Stainless steel, NO, pilot operated, 230 V, 50 Hz, Medium temp. max. 80°C/90°C, G 1/2, PN 0.5-7 bar. Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1561 ES
Article number	116564
EAN/barcode	 4047322324380
Your price	122,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	70.0 mm
C	112.3 mm
DN	15
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. operating pressure	7 bar
Min. operating pressure	0.5 bar
Page No.	HK331
Page No. AS	AS051
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/2
Type	4
Valve seat	Stainless steel 1.4301

Variants

Article number	Thread	DN	Price
116564	G 1/2	15	122,65 € / Stk
116566	G 3/4	20	147,57 € / Stk
116568	G 1	25	179,18 € / Stk

More Pictures

