

Datasheet for: 100567


Service unit 2-part »multifix« with PC container, Size 1, G 3/8

Service unit 2-part »multifix« with polycarbonate container, Size 1, G 3/8, Input pressure max. 16 bar, Control range 0.5 - 10 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number CL 12 K-HA

Article number 100567

EAN/barcode



4047322345262

Your price 90,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	92.8 mm
B	192.1 mm
Bowl	Polycarbonate container
C	67.0 mm
Condensate drain	Semi-automatic
D	125.1 mm
DN	10.0
Filter rating	5.0 μ m
Flow rate	1100 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK091
Page No. TS	TS003

Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Sight dome	PA
Size	1
Spring bonnet	POM-brass
Thread	G 3/8

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100567	G 3/8	Die-cast zinc	5.0 μm	1100 l/min	1	10.0	90,78 € / Stk
100570	G 1	Aluminium	40.0 μm	10500 l/min	5	25.0	469,14 € / Stk
100569	G 3/4	Die-cast zinc	5.0 μm	3500 l/min	3	20.0	152,96 € / Stk
100566	G 1/4	Die-cast zinc	5.0 μm	1100 l/min	1	6.0	86,75 € / Stk
100568	G 1/2	Die-cast zinc	5.0 μm	3500 l/min	3	15.0	152,96 € / Stk

More Pictures

