

Datasheet for: 100717



Service unit 2-part »variobloc« with PC container, Size 1, G 1/4

Service unit 2-part »variobloc« with PC container, Size 1, G 1/4, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 22
Article number	100717
EAN/barcode	 4047322170192
Your price	102,90 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	96.0 mm
B	203.0 mm
Bowl	Polycarbonate container
C	68.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 µm
Flow rate	1500 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	HK109

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	1
Spring bonnet	POM
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Size	Price
100717	G 1/4	1500 l/min	1	102,90 € / Stk
100718	G 3/8	1800 l/min	1	102,90 € / Stk
100719	G 1/2	3400 l/min	2	161,38 € / Stk
100720	G 3/4	5000 l/min	2	161,38 € / Stk
100721	G 1	5000 l/min	2	197,44 € / Stk

More Pictures

