

Datasheet for: 103277


Ball valve heavy duty design, Manual lever, IT/ET, G/R 1 1/2

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1 1/2, PN max. 80 bar . Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Type number	3350.88
Article number	103277
EAN/barcode	 4047322216197
Your price	91,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	150.0 mm
B	103.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	40.0
E	21.2 mm
F	18.0 mm
Hand lever	Aluminium, painted black
Housing	Nickel-plated brass
L	114.5 mm
Max. operating temperature	130 °C
Min. operating temperature	-20 °C
PN	80 bar
Page No.	HK273
Standard thread	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stem seal	PTFE
Thread	G/R 1 1/2
Thread material	Brass with a bare metal surface
a/f 1	56.0 mm
a/f 2	57.0 mm

Variants

Article number	Thread	DN	a/f 1	a/f 2	Price
103277	G/R 1 1/2	40.0	56.0 mm	57.0 mm	91,09 € / Stk
103276	G/R 1 1/4	32.0	49.0 mm	50.0 mm	72,91 € / Stk
103275	G/R 1	25.0	39.0 mm	40.0 mm	49,28 € / Stk
103273	G/R 1/2	15.0	26.0 mm	27.0 mm	20,51 € / Stk
103278	G/R 2	50.0	69.0 mm	70.0 mm	157,03 € / Stk
103274	G/R 3/4	20.0	32.0 mm	33.0 mm	31,34 € / Stk
103272	G/R 3/8	10.0	21.0 mm	21.0 mm	16,32 € / Stk
103271	G/R 1/4	8.0	18.0 mm	18.0 mm	13,63 € / Stk

More Pictures

