


Datasheet for: 158826


End position feedback, SPDT microswitch, plastic, 4V DC-250 V AC

End position feedback, with microswitch, plastic, SPDT switch, 4V DC - 250 V AC, Changeover type, 1mA-5mA, IP67, Temp. -20°C to 80°C . Robust type in a plastic housing - Universal indicator for NAMUR sizes 80 x 30 and 130 x 30 - Height-adjustable feet that adapt to different pinion projections - ON / OFF position indicator also visible from a distance - Easy-to-adjust, self-locking trip cam

Type number	350.911-1
Article number	158826
EAN/barcode	 4047322644624
Your price	91,20 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Cable gland	M20x1.5
Cap	Transparent plastic lid
Current range	max. 5 A
Description	SPDT - double microswitch
Housing	Fiberglass reinforced plastic
Max. temperature range	80 °C
Min. temperature range	-20 °C
Minimum switching capacity	50 mA at 24 V DC
Nominal switching capacity	50 mA to 5 A at 250 V AC
Page No.	HK314
Protection IP	IP 67, acc. to DIN EN 60529
Switching function	Changeover, silver-plated contacts
Version	with microswitch