


## Datasheet for: 100798


**Service unit 2-part »Standard-mini« with PC container, G 1/4**

Service unit 2-part »Standard-mini«, PC container and pressure gauge, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar . Compact, two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	824 K
Article number	100798
EAN/barcode	 4047322120678
Your price	91,36 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	85.0 mm
B	167.0 mm
Bowl	Polycarbonate container
C	65.0 mm
Condensate drain	semi-automatic
D	102.0 mm
DN	5.0
Filter rating	5.0 $\mu$ m
Flow rate	350 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK118
Pressure gauge display max.	16.0 bar

Pressure gauge	0.0 bar
display min.	NBR
Sealant	Standard-mini
Series	PA
Sight dome	G 1/4
Thread	

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
100798	G 1/4	91,36 € / Stk
100797	G 1/8	91,36 € / Stk

## More Pictures

