

Datasheet for: 116112


3/2-way valve, electropneumatic, »3V«, bistable, G 1/8, 24 V DC

 3/2-way valve, electropneumatic, »3V«, bistable, G 1/8, 24 V DC, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C .
 3/2-way pilot valves - Electro-pneumatic -

Type number	517.1401
Article number	116112
EAN/barcode	 4047322310321
Your price	91,37 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	500 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Bistable
Page No.	HK467
Page No. AS	AS086
Protection IP	IP 65
Size	100
Symbol	34
Valve body	Aluminium alloy
Voltage	24 V DC

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116112	G 1/8	G 1/8	24 V DC	500 l/min	100	91,37 € / Stk
116111	M5	M5	24 V DC	300 l/min	100	91,37 € / Stk
116116	G 3/8	G 3/8	24 V DC	1500 l/min	300	95,44 € / Stk
116115	G 1/4	G 1/4	24 V DC	1300 l/min	300	95,44 € / Stk
116114	G 1/4	G 1/4	24 V DC	850 l/min	200	93,11 € / Stk
116113	G 1/8	G 1/8	24 V DC	750 l/min	200	93,11 € / Stk
116122	G 3/8	G 3/8	230 V, 50 Hz	1500 l/min	300	95,44 € / Stk
116121	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	95,44 € / Stk
116120	G 1/4	G 1/4	230 V, 50 Hz	850 l/min	200	93,11 € / Stk
116118	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	91,37 € / Stk
116117	M5	M5	230 V, 50 Hz	300 l/min	100	91,37 € / Stk
116119	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	93,11 € / Stk

More Pictures

