


Datasheet for: 100959



Filter »Standard«, Polycarbonate container, 5 µm, Size 3, G 1

Filter »Standard« with polycarbonate container, 5 µm, Size 3, G 1, Input pressure max. 16 bar, Med. / ambient temp. max. 60 °C . Centrifugal separators with a sintered filter element.

Type number	650 E/K-HA
Article number	100959
EAN/barcode	 4047322338103
Your price	103,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	90.0 mm
Bowl	Polycarbonate container
C	26.5 mm
Condensate drain	Semi-automatic
D	169.9 mm
DN	25.0
Filter rating	5.0 µm
Flow rate	4000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
H	50.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK125
Series	Standard
Size	3
Thread	G 1

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
100959	G 1	5.0 μm	4000 l/min	3	25.0	103,58 € / Stk
100961	G 1 1/2	40.0 μm	12500 l/min	4	45.0	191,83 € / Stk
100954	G 1/4	5.0 μm	800 l/min	1	6.0	24,45 € / Stk
100960	G 1 1/4	40.0 μm	12500 l/min	4	40.0	231,35 € / Stk
100962	G 2	60.0 μm	30000 l/min	5	55.0	549,33 € / Stk
100956	G 3/8	40.0 μm	3100 l/min	2	10.0	44,99 € / Stk
100957	G 1/2	5.0 μm	4000 l/min	3	15.0	44,99 € / Stk
100958	G 3/4	5.0 μm	4000 l/min	3	20.0	104,60 € / Stk
100955	G 3/8	5.0 μm	800 l/min	1	6.0	24,45 € / Stk

More Pictures

