


## Datasheet for: 103724


**Blocking valve pneumat. actuated, double-acting, NC, NBR, Rp 1/2**

Blocking valve pneumat. actuated, double-acting, NC, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 3-8 bar, Rp 1/2 . 2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. These valves have a full bore and - owing to the optimised design - only minimal flow losses. They are controlled by means of filtered compressed air.

Type number	351.912
Article number	103724
EAN/barcode	 4047322079037
Your price	103,67 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	NAMUR interface, direct: 2 x G 1/8
DN	15.0
H	51.7 mm
Housing	Nickel-plated brass
Internal parts	Nickel-plated brass
L	112.0 mm
Max. operating pressure	10 bar
Max. operating temperature	80 °C
Max. pilot pressure	8.0 bar
Min. operating temperature	-20 °C
Min. pilot pressure	3.0 bar
Mounting position	Any
Page No.	HK344
Sealant	NBR
Spring	Stainless steel
Thread	Rp 1/2
Version	double-acting

## Variants

Article number	Thread	DN	Price
103724	Rp 1/2	15.0	103,67 € / Stk
103723	Rp 3/8	10.0	94,71 € / Stk
103725	Rp 3/4	20.0	117,18 € / Stk
103726	Rp 1	25.0	134,66 € / Stk
133388	Rp 1 1/4	32.0	205,56 € / Stk
133390	Rp 2	50.0	355,28 € / Stk
133389	Rp 1 1/2	40.0	255,47 € / Stk

## More Pictures

