

Datasheet for: 108114


Kamlok quick-connect socket with ET, B type, 1.4401, R 4

Kamlok quick-connect socket with exterior thread, B type, Stainless steel 1.4401, R 4, for plug Ø 120 mm, Pressure max. 16 bar . High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc. All female threaded couplings and connectors are with female thread sealing ring made of PTFE.

Type number	1113.40-ES
Article number	108114
EAN/barcode	 4047322404464
Your price	91,89 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	159.9 mm
C	88.5 mm
For plug Ø	120.0 mm
Max. operating pressure	16 bar
Max. temperature range	95 °C
Min. temperature range	-20 °C
Page No.	HK623
Sealant	NBR, resistant to oils and benzine
Thread	R 4

Variants

Article number	Thread	For plug Ø	Price
108114	R 4	120.0 mm	91,89 € / Stk
108111	R 2	64.0 mm	39,37 € / Stk
108110	R 1 1/2	54.0 mm	28,56 € / Stk
108107	R 3/4	32.0 mm	13,41 € / Stk
108109	R 1 1/4	46.0 mm	25,49 € / Stk
108113	R 3	92.0 mm	70,94 € / Stk
108112	R 2 1/2	76.5 mm	53,09 € / Stk
108108	R 1	37.0 mm	17,89 € / Stk

More Pictures

