

## Datasheet for: 106566



### 5/2-way valve, electropneum. bistable G 3/8, 230 V, 50 Hz

5/2-way valve, Differen. piston, electropneum. bistable G 3/8, 230 V, 50 Hz, Operating pre. 1-10 bar, Operating temp. -10°C to 60°C .

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 517.225-38                                                                                         |
| Article number | 106566                                                                                             |
| EAN/barcode    | <br>4047322386159 |
| Your price     | 124,80 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                         |                                           |
|-------------------------|-------------------------------------------|
| Connection              | G 3/8                                     |
| DN                      | 13.3                                      |
| Flow rate 1             | 1560 NI/min                               |
| Flow rate 2             | 2150 NI/min                               |
| Flow rate measurement 1 | Flow rate at 6 bar and $\Delta p$ 0.5 bar |
| Flow rate measurement 2 | Flow rate at 6 bar and $\Delta p$ 1.0 bar |
| Function                | 5/2                                       |
| Manual control          | latching                                  |
| Max. operating pressure | 10 bar                                    |
| Max. temperature range  | 60 °C                                     |
| Min. operating pressure | 1 bar                                     |
| Min. temperature range  | -10 °C                                    |
| Operation               | Bistable                                  |
| Page No.                | HK471                                     |
| Symbol                  | 36                                        |
| Voltage                 | 230 V, 50 Hz                              |

## Variants

| Article number | Connection | Voltage      | DN   | Flow rate 1 | Flow rate 2 | Price          |
|----------------|------------|--------------|------|-------------|-------------|----------------|
| 106566         | G 3/8      | 230 V, 50 Hz | 13.3 | 1560 NI/min | 2150 NI/min | 124,80 € / Stk |
| 106560         | G 1/8      | 24 V DC      | 5.0  | 400 NI/min  | 550 NI/min  | 110,67 € / Stk |
| 106561         | G 1/4      | 24 V DC      | 7.5  | 750 NI/min  | 1100 NI/min | 114,45 € / Stk |
| 106563         | G 1/2      | 24 V DC      | 15.0 | 3200 NI/min | 4600 NI/min | 226,53 € / Stk |
| 106564         | G 1/8      | 230 V, 50 Hz | 5.0  | 400 NI/min  | 550 NI/min  | 110,67 € / Stk |
| 106565         | G 1/4      | 230 V, 50 Hz | 7.5  | 750 NI/min  | 1100 NI/min | 114,45 € / Stk |
| 106567         | G 1/2      | 230 V, 50 Hz | 15.0 | 3200 NI/min | 4600 NI/min | 226,53 € / Stk |
| 106562         | G 3/8      | 24 V DC      | 13.3 | 1560 NI/min | 2150 NI/min | 124,80 € / Stk |

## More Pictures

