

Datasheet for: 142452



Microfilter »FUTURA-mini« with metal container, Size 0, G 1/4

Microfilter »FUTURA-mini«, Metal container, 0.01 μm , Size 0, G 1/4, Input pressure 1.5 - 12 bar, Temp. -10°C to 50°C, Fully-autom. . Micro-filters in modern design for compliance with strict compressed air purity requirements. Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 μm from compressed air and gases.

Type number	FUM 881-M
Article number	142452
EAN/barcode	 4047322556774
Your price	125,40 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	43.0 mm
B	160.0 mm
Bowl	Metal container
C	27.0 mm
Condensate drain	Fully-automatic
Connecting thread	Plastic
Dust separation	> 0.01 μm 99.999 %
Filter element	Borosilicate glass fibre
Filter rating	0.01 μm
Flow rate	190 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.1$ bar
Housing	PA66 GF60
Max. input pressure	12 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	1.5 bar
Min. temperature range	-10 °C
Page No.	HK014
Residual oil content	< 0.01 mg/m ³

Sealant
 Series
 Thread

NBR
 FUTURA-mini
 G 1/4

Variants

Article number	Condensate drain	Price
142452	Fully-automatic	125,40 € / Stk
142451	Semi-automatic	79,96 € / Stk

More Pictures

