


Datasheet for: 103665


Throttle plate for NAMUR valves, 5-way, Knurled screw

Throttle plate for NAMUR valves, Anodised aluminium, Temp. -20 °C to 70 °C, Working pressure 0.5 - 10 bar, 5-way, Knurled screw . Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Type number	551.51
Article number	103665
EAN/barcode	 4047322272544
Your price	93,08 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

DN	5.0
Flow rate	650 l/min
Function	5-way
Housing	Aluminium anodised
Max. operating temperature	70 °C
Max. working pressure	10 bar
Medium	Air, neutral gases (filtered)
Min. operating temperature	-20 °C
Min. working pressure	0.5 bar
Operation	Knurled screw
Page No.	HK312
Scope of delivery	1 coding pin, 2 O-rings, 2 fixing screws
Sealant	NBR

Variants

<i>Article number</i>	<i>Function</i>	<i>Operation</i>	<i>Price</i>
103665	5-way	Knurled screw	93,08 € / Stk
103664	3-way	Screwdriver	93,08 € / Stk
103663	3-way	Knurled screw	93,08 € / Stk
103666	5-way	Screwdriver	93,08 € / Stk

More Pictures

