

Datasheet for: 116168


5/3-way valve, electropneumatic, »4V« Centre vented, 24 V DC

5/3-way valve, electropneumatic, »4V«, Centre vented, G 1/4, 24 V DC, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C . 5/3-way pilot valves - Electro-pneumatic -

Type number	517.3203
Article number	116168
EAN/barcode	 4047322310932
Your price	105,80 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Mid-position exhausted
Page No.	HK469
Page No. AS	AS088
Protection IP	IP 65
Size	200
Symbol	38
Valve body	Aluminium alloy
Voltage	24 V DC

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116168	G 1/4	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116165	M5	M5	24 V DC	250 l/min	100	101,14 € / Stk
116173	G 1/8	G 1/8	230 V, 50 Hz	400 l/min	100	101,14 € / Stk
116172	M5	M5	230 V, 50 Hz	250 l/min	100	101,14 € / Stk
116171	G 1/2	G 1/2	24 V DC	1600 l/min	400	158,29 € / Stk
116170	G 3/8	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116169	G 1/4	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116177	G 3/8	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116178	G 1/2	G 1/2	230 V, 50 Hz	1600 l/min	400	158,29 € / Stk
116175	G 1/4	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116174	G 1/8	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116176	G 1/4	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116167	G 1/8	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116166	G 1/8	G 1/8	24 V DC	400 l/min	100	101,14 € / Stk

More Pictures

