

Datasheet for: 116120


3/2-way valve, electropneumatic, »3V«, bistable, 230 V, 50 Hz

 3/2-way valve, electropneumatic, »3V«, bistable, G 1/4, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C .
 3/2-way pilot valves - Electro-pneumatic -

Type number	517.1503
Article number	116120
EAN/barcode	 4047322310413
Your price	93,11 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/4
Flow rate	850 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Bistable
Page No.	HK467
Page No. AS	AS086
Protection IP	IP 65
Size	200
Symbol	34
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116120	G 1/4	G 1/4	230 V, 50 Hz	850 l/min	200	93,11 € / Stk
116111	M5	M5	24 V DC	300 l/min	100	91,37 € / Stk
116112	G 1/8	G 1/8	24 V DC	500 l/min	100	91,37 € / Stk
116116	G 3/8	G 3/8	24 V DC	1500 l/min	300	95,44 € / Stk
116115	G 1/4	G 1/4	24 V DC	1300 l/min	300	95,44 € / Stk
116114	G 1/4	G 1/4	24 V DC	850 l/min	200	93,11 € / Stk
116113	G 1/8	G 1/8	24 V DC	750 l/min	200	93,11 € / Stk
116122	G 3/8	G 3/8	230 V, 50 Hz	1500 l/min	300	95,44 € / Stk
116121	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	95,44 € / Stk
116118	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	91,37 € / Stk
116117	M5	M5	230 V, 50 Hz	300 l/min	100	91,37 € / Stk
116119	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	93,11 € / Stk

More Pictures

