

Datasheet for: 116189


5/3-way valve, electropneumatic »4V« Centre aerated, 230 V, 50 Hz

5/3-way valve, electropneumatic, »4V«, Centre aerated, G 1/4, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C . 5/3-way pilot valves - Electro-pneumatic -

Type number	517.3503
Article number	116189
EAN/barcode	 4047322311250
Your price	105,80 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Mid-position pressurised
Page No.	HK470
Page No. AS	AS088
Protection IP	IP 65
Size	200
Symbol	39
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116189	G 1/4	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116190	G 1/4	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116181	G 1/8	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116180	G 1/8	G 1/8	24 V DC	400 l/min	100	101,14 € / Stk
116183	G 1/4	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116182	G 1/4	G 1/8	24 V DC	550 l/min	200	105,80 € / Stk
116185	G 1/2	G 1/2	24 V DC	1600 l/min	400	158,29 € / Stk
116184	G 3/8	G 1/4	24 V DC	950 l/min	300	115,23 € / Stk
116186	M5	M5	230 V, 50 Hz	250 l/min	100	101,14 € / Stk
116188	G 1/8	G 1/8	230 V, 50 Hz	550 l/min	200	105,80 € / Stk
116191	G 3/8	G 1/4	230 V, 50 Hz	950 l/min	300	115,23 € / Stk
116187	G 1/8	G 1/8	230 V, 50 Hz	400 l/min	100	101,14 € / Stk
116192	G 1/2	G 1/2	230 V, 50 Hz	1600 l/min	400	158,29 € / Stk
116179	M5	M5	24 V DC	250 l/min	100	101,14 € / Stk

More Pictures

