

Datasheet for: 101059



Service unit 2-part »Standard«, Metal container, Size 1, G 3/8

Service unit 2-part »Standard«, Metal container, metal drip cap, Size 1, G 3/8, Input press. max. 25 bar, Control range 0.5-16 bar. Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	827 M
Article number	101059
EAN/barcode	 4047322120845
Your price	126,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	117.0 mm
B	240.0 mm
Bowl	Metal container
C	106.5 mm
Condensate drain	Manuel
DN	6.0
Filter rating	5.0 µm
Flow rate	600 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	16.0 bar
Max. input pressure	25 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK130
Pressure gauge display max.	25.0 bar

Pressure gauge display min.	0.0 bar
Pressure gauge Ø	50 mm
Sealant	NBR
Series	Standard
Sight dome	Zinc-glass-NBR
Size	1
Thread	G 3/8

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
101059	G 3/8	5.0 µm	600 l/min	1	6.0	126,65 € / Stk
101058	G 1/4	5.0 µm	600 l/min	1	6.0	126,65 € / Stk
101060	G 3/8	40.0 µm	800 l/min	2	10.0	203,71 € / Stk
101061	G 1/2	5.0 µm	2100 l/min	3	15.0	203,71 € / Stk
101062	G 3/4	40.0 µm	4000 l/min	4	20.0	415,29 € / Stk
101063	G 1	40.0 µm	4000 l/min	4	25.0	415,29 € / Stk

More Pictures

