


Datasheet for: 107112


Quick-connect coupling I.D. 2.7, St. steel 1.4404, Sleeve I.D. 4

Quick-connect coupling I.D. 2.7, Stainless steel 1.4404, Sleeve I.D. 4, Operating pressure - 35 bar, Temp. -15 °C to 200 °C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Type number	243.08/6-ES
Article number	107112
EAN/barcode	 4047322403917
Your price	106,24 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel 1.4404
Connection	I.D. 4
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Stainless steel 1.4404
Length	35.0 mm
Max. ambient temperature	200 °C
Max. medium temperature	200 °C
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	WEB
Page No. SK	SK008
Retaining ring	Stainless steel 1.4404
Sealant	FKM
Sleeve	Stainless steel 1.4404

Spring
Valve body

Stainless steel 1.4404
Stainless steel 1.4404

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107112	I.D. 4	106,24 € / Stk
107111	I.D. 3	88,57 € / Stk

More Pictures

