


Datasheet for: 102963


3/2-way solenoid valve, NC, directly operated 230 V, 50 - 60 Hz

3/2-way solenoid valve brass, NC, directly operated 230 V, 50 - 60 Hz, Sealing material NBR, Rp 1/8, PN - 7 bar, I.D. 2.4 . For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 3211
Article number	102963
EAN/barcode	 4047322160698
Your price	106,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	75.0 mm
B	30.0 mm
DN	2.4
Electrical connection	For Pg 11P connector socket acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	75 °C
Max. medium temperature	90 °C
Max. operating pressure	7 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK327
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 1/8
Type	7
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	DN	Type	Price
102963	Rp 1/8	7 bar	2.4	7	106,28 € / Stk
102964	Rp 1/4	6 bar	3.2	10	137,43 € / Stk

More Pictures

