

Datasheet for: 101092



Combi-service unit with PC container, Size 1, G 1/2, 0.5 - 10 bar

Combi-service unit with PC container, manual bleeder valve, Size 1, G 1/2, Input pressure max. 16 bar, Control range 0.5 - 10 bar. A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design. The pressure setting can be locked by pushing the knob down. Oil can be filled under pressure.

Type number	810.07 K
Article number	101092
EAN/barcode	 4047322119405
Your price	127,54 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	65.0 mm
B	217.0 mm
Bowl	Polycarbonate container
C	68.5 mm
Condensate drain	Manual drain valve
Filter rating	50.0 μ m
Flow rate	1400 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	HK134
Sealant	NBR
Sight dome	PA
Size	1

Spring bonnet
Thread

PA
G 1/2

Variants

Article number	Thread	Max. control range	Flow rate	Size	Price
101092	G 1/2	10.0 bar	1400 l/min	1	127,54 € / Stk
101088	G 1/4	10.0 bar	1400 l/min	1	128,83 € / Stk
101089	G 1/4	16.0 bar	1000 l/min	1	128,83 € / Stk
101090	G 3/8	10.0 bar	1400 l/min	1	128,60 € / Stk
101091	G 3/8	16.0 bar	1000 l/min	1	128,60 € / Stk
101093	G 1/2	16.0 bar	1000 l/min	1	127,54 € / Stk
101094	G 3/4	10.0 bar	3400 l/min	2	212,24 € / Stk
101095	G 3/4	16.0 bar	2800 l/min	2	212,24 € / Stk
101096	G 1	10.0 bar	3400 l/min	2	209,57 € / Stk
101097	G 1	16.0 bar	2800 l/min	2	209,57 € / Stk

More Pictures

