


Datasheet for: 100802


Service unit 3-part »Standard-mini« with PC container, G 1/4

Service unit 3-part »Standard-mini«, PC container and pressure gauge, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar . Compact, three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	845.02 K
Article number	100802
EAN/barcode	 4047322121187
Your price	93,45 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	130.0 mm
B	151.5 mm
Bowl	Polycarbonate container
C	49.5 mm
Condensate drain	semi-automatic
D	102.0 mm
DN	5.0
Filter rating	5.0 μm
Flow rate	300 l/min
Flow rate measurement	At $P_1 = 8 \text{ bar}$, $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK119
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	Standard-mini
Sight dome	PA
Thread	G 1/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
100802	G 1/4	93,45 € / Stk
100801	G 1/8	93,45 € / Stk

More Pictures

