


## Datasheet for: 158075


**Check valve, DN 25, Red brass, G 1, PN max. 16 bar**

Check valve, DN 25, Red brass, Metallic sealing, Operating temperature -10 °C to 80 °C, G 1, PN max. 16 bar .

Applications: Water (no steam), neutral and non-corrosive liquid media, mineral oils. Only suitable for liquid media. Flap valve closes by gravity, therefore only possible to be installed horizontally!

Type number	RK1RG
Article number	158075
EAN/barcode	 4047322631594
Your price	107,80 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

DN	25.0
Housing	Red brass
Length	80.0 mm
Max. operating pressure	16 bar
Max. operating temperature	80 °C
Min. operating temperature	-10 °C
Page No.	HK359
Standard thread	G-thread acc. to DIN EN ISO 228-1
Thread	G 1
Valve disc a/f	Brass 41 mm

**Variants**

Article number	Thread	DN	a/f	Price
158075	G 1	25.0	41 mm	107,80 € / Stk

## Variants

Article number	Thread	DN	a/f	Price
158074	G 3/4	20.0	34 mm	90,56 € / Stk
158077	G 1 1/2	40.0	55 mm	181,56 € / Stk
158079	G 2 1/2	65.0	90 mm	1.117,16 € / Stk
158078	G 2	50.0	70 mm	252,64 € / Stk
158076	G 1 1/4	32.0	51 mm	141,92 € / Stk
158073	G 1/2	15.0	27 mm	72,96 € / Stk

## More Pictures

