


Datasheet for: 100996


Special filter »Standard« Protective cage, 0.01 μm , Size 2, G 3/8

Special filter »Standard« with polycarbonate container and protective cage, 0.01 μm , Size 2, G 3/8, Input pressure max. 16 bar . For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Type number	675 S
Article number	100996
EAN/barcode	 4047322111775
Your price	93,77 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
Bowl	Polycarbonate container with protective cage
C	16.0 mm
Condensate drain	Semi-automatic
D	145.7 mm
DN	10.0
Efficiency	99.999 %
Filter rating	0.01 μm
Flow rate	720 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
H	50.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK127
Series	Standard
Size	2
Thread	G 3/8

Variants

Article number	Thread	Flow rate	Size	DN	Condensate drain	Price
100996	G 3/8	720 l/min	2	10.0	Semi-automatic	93,77 € / Stk
100994	G 1/4	380 l/min	1	6.0	Semi-automatic	69,54 € / Stk
100995	G 3/8	380 l/min	1	6.0	Semi-automatic	81,19 € / Stk
100997	G 1/2	1250 l/min	3	15.0	Semi-automatic	128,94 € / Stk
100998	G 3/4	7000 l/min	4	20.0	Manuel	303,45 € / Stk
100999	G 1	7000 l/min	4	25.0	Manuel	303,45 € / Stk

More Pictures

