

Datasheet for: 101072



Service unit 3-part »Standard«, Protective cage, Size 1, G 1/4

Service unit 3-part »Standard«, PC container, protective cage, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5-10 bar. Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	845 B/S
Article number	101072
EAN/barcode	 4047322121132
Your price	133,61 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	172.0 mm
B	182.6 mm
Bowl	Polycarbonate container with protective cage
C	51.0 mm
Condensate drain	Semi-automatic
DN	6.0
Filter rating	5.0 µm
Flow rate	600 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK132
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar

Pressure gauge	50 mm
Ø	
Sealant	NBR
Series	Standard
Sight dome	PA
Size	1
Thread	G 1/4

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
101072	G 1/4	5.0 µm	600 l/min	1	6.0	133,61 € / Stk
101073	G 3/8	5.0 µm	600 l/min	1	6.0	133,61 € / Stk
101074	G 3/8	40.0 µm	1400 l/min	2	6.0	186,83 € / Stk
101075	G 1/2	5.0 µm	3200 l/min	3	15.0	214,80 € / Stk
101076	G 3/4	5.0 µm	3200 l/min	3	20.0	397,35 € / Stk
101077	G 1	5.0 µm	3200 l/min	3	25.0	397,35 € / Stk
101078	G 1 1/4	40.0 µm	5000 l/min	4	25.0	788,74 € / Stk
101079	G 1 1/2	40.0 µm	5000 l/min	4	35.0	751,70 € / Stk

More Pictures

