


Datasheet for: 158094



3/2-way solenoid valve stainless steel, NC, 24 V DC, FPM, G 1/8

3/2-way solenoid valve, Stainless steel, NC, Directly operated, 24 V DC, Medium temp. -10 °C to 100 °C, FPM, G 1/8, PN - 15 bar .

Type number	MV18ES24
Article number	158094
EAN/barcode	 4047322631808
Your price	128,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	60.5 mm
B	33.0 mm
DN	1.2
Electrical connection	for connector socket PG 11 P, acc. to DIN 4400
Function	NC
Housing	Stainless steel 1.4401
Internal parts	Stainless steel
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Max. operating pressure	15 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK331
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/8
Valve seat	Stainless steel 1.4401
Voltage	24 V DC

Variants

Article number	Voltage	Price
158094	24 V DC	128,18 € / Stk
158093	230 V AC, 50 - 60 Hz	128,18 € / Stk

More Pictures

