


Datasheet for: 142444


Pre-filter »FUTURA-mini« with PC container, 0.3 µm, Size 0, G 1/4

Pre-filter »FUTURA-mini« with PC container, 0.3 µm, Size 0, G 1/4, PE 1.5 - 12 bar, Temp. -10 °C to 50 °C, Fully-automatic . Pre-filters in modern design for compliance with strict compressed air purity requirements. Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Type number	FUM 861
Article number	142444
EAN/barcode	 4047322556699
Your price	108,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	43.0 mm
B	170.0 mm
Bowl	Polycarbonate container
C	27.0 mm
Condensate drain	Fully-automatic
Connecting thread	Plastic
Filter element	Impregnated paper
Filter rating	0.3 µm
Flow rate	140 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Housing	PA66 GF60
Max. input pressure	12 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. input pressure	1.5 bar
Min. temperature range	-10 °C
Page No.	HK013
Sealant	NBR
Series	FUTURA-mini

Thread

G 1/4

Variants

Article number	Condensate drain	Price
142444	Fully-automatic	108,34 € / Stk
142443	Semi-automatic	65,87 € / Stk
142445	Fully-automatic (NC)	123,06 € / Stk

More Pictures
