


Datasheet for: 116571


2/2-way solenoid valve »2KW« NO, pilot operated, 24 V DC, G 3/4

2/2-way solenoid valve »2KW«, Brass, NO, pilot operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 3/4, PN 0.5 - 7 bar . Standard series available in two different versions:
 -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1572
Article number	116571
EAN/barcode	 4047322325158
Your price	108,44 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	82.0 mm
C	120.8 mm
DN	20
Housing	Brass
Internal parts	Stainless steel
Max. operating pressure	7 bar
Min. operating pressure	0.5 bar
Page No.	HK326
Page No. AS	AS048
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 3/4
Type	4
Valve seat	Brass

Variants

Article number	Thread	DN	Price
116571	G 3/4	20	108,44 € / Stk
116573	G 1	25	117,13 € / Stk
116569	G 1/2	15	80,01 € / Stk

More Pictures

