


Datasheet for: 116349


3/2-way start-up valve »G«, 24 V DC, Size 300, G 1/2

3/2-way start-up valve »G«, 24 V DC, with mounting bracket and silencer, Size 300, G 1/2, Input pressure 2.5 - 9 bar . Combined shut-off and pressure build-up valve (start-up valve). Operated by secondary pressure for controlled pressurisation of pneumatic systems. The 3/2-way valve opens when the solenoid is activated. The full cross-section of the valve is open when the working pressure is 50% of the input pressure. When the solenoid is deactivated, the 3/2-way valve closes and the pressure in the line is exhausted via the regulator. With adjustable restrictor.

Type number	GA 13.2
Article number	116349
EAN/barcode	 4047322308755
Your price	93,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	65.0 mm
B	131.0 mm
C	97.0 mm
D	34.0 mm
Electrical connection	Device plug PG 9, type B
Flow rate	2500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. input pressure	9 bar
Max. medium temperature	70 °C
Min. input pressure	2.5 bar
Page No.	WEB
Sealant	NBR
Series	G
Size	300
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	Price
116349	G 1/2	2500 l/min	300	93,99 € / Stk
116345	G 1/4	1600 l/min	300	93,99 € / Stk
116347	G 3/8	2500 l/min	300	93,99 € / Stk
116353	G 1/2	4500 l/min	400	115,92 € / Stk
116351	G 3/8	4500 l/min	400	115,92 € / Stk

More Pictures

