


Datasheet for: 116139


5/2-way valve, electropneumatic, »4V«, bistable, G 1/8, 24 V DC

 5/2-way valve, electropneumatic, »4V«, bistable, G 1/8, 24 V DC, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C .
 5/2-way pilot valves - Electro-pneumatic -

Type number	517.2202
Article number	116139
EAN/barcode	 4047322310642
Your price	94,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Bistable
Page No.	HK468
Page No. AS	AS087
Protection IP	IP 65
Size	200
Symbol	36
Valve body	Aluminium alloy
Voltage	24 V DC

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116139	G 1/8	G 1/8	24 V DC	750 l/min	200	94,29 € / Stk
116142	G 3/8	G 1/4	24 V DC	1500 l/min	300	97,77 € / Stk
116147	G 1/4	G 1/8	230 V, 50 Hz	850 l/min	200	94,29 € / Stk
116148	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	102,42 € / Stk
116146	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	94,29 € / Stk
116150	G 1/2	G 1/2	230 V, 50 Hz	2000 l/min	400	140,13 € / Stk
116149	G 3/8	G 1/4	230 V, 50 Hz	1500 l/min	300	102,42 € / Stk
116144	M5	M5	230 V, 50 Hz	300 l/min	100	92,53 € / Stk
116138	G 1/8	G 1/8	24 V DC	500 l/min	100	92,53 € / Stk
116137	M5	M5	24 V DC	300 l/min	100	92,53 € / Stk
116143	G 1/2	G 1/2	24 V DC	2000 l/min	400	110,58 € / Stk
116141	G 1/4	G 1/4	24 V DC	1300 l/min	300	97,77 € / Stk
116140	G 1/4	G 1/8	24 V DC	850 l/min	200	94,29 € / Stk
116145	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	92,53 € / Stk

More Pictures

