

Datasheet for: 116146


5/2-way valve, electropneumatic, »4V«, bistable, 230 V, 50 Hz

 5/2-way valve, electropneumatic, »4V«, bistable, G 1/8, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C .
 5/2-way pilot valves - Electro-pneumatic -

Type number	517.2302
Article number	116146
EAN/barcode	 4047322310710
Your price	94,29 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Bistable
Page No.	HK468
Page No. AS	AS087
Protection IP	IP 65
Size	200
Symbol	36
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116146	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	94,29 € / Stk
116142	G 3/8	G 1/4	24 V DC	1500 l/min	300	97,77 € / Stk
116139	G 1/8	G 1/8	24 V DC	750 l/min	200	94,29 € / Stk
116147	G 1/4	G 1/8	230 V, 50 Hz	850 l/min	200	94,29 € / Stk
116148	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	102,42 € / Stk
116150	G 1/2	G 1/2	230 V, 50 Hz	2000 l/min	400	140,13 € / Stk
116149	G 3/8	G 1/4	230 V, 50 Hz	1500 l/min	300	102,42 € / Stk
116144	M5	M5	230 V, 50 Hz	300 l/min	100	92,53 € / Stk
116138	G 1/8	G 1/8	24 V DC	500 l/min	100	92,53 € / Stk
116137	M5	M5	24 V DC	300 l/min	100	92,53 € / Stk
116143	G 1/2	G 1/2	24 V DC	2000 l/min	400	110,58 € / Stk
116141	G 1/4	G 1/4	24 V DC	1300 l/min	300	97,77 € / Stk
116140	G 1/4	G 1/8	24 V DC	850 l/min	200	94,29 € / Stk
116145	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	92,53 € / Stk

More Pictures

