


## Datasheet for: 139310


**3/2-way valve »FUTURA«, pneumatically actuated, Size 2, G 1/2**

3/2-way valve »FUTURA«, pneumatically actuated, Size 2, G 1/2, Exhaust G 1/2, Input pressure max. 16 bar, Temp. -10 °C to 50 °C . Pneumatic systems or parts of systems can be switched on and off by means of an pneumatic signal. 3/2-way type including silencer. When they are switched off, the system is exhausted at the same time.

Type number	FU 968-137
Article number	139310
EAN/barcode	 4047322531092
Your price	94,70 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	63.0 mm
B	117.6 mm
C	61.1 mm
Connecting thread	Material: Die-cast zinc
Exhaust air	G 1/2
Flow rate	4500 l/min
Flow rate measurement	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Page No.	HK057
Series	FUTURA
Size	2
Thread	G 1/2

## Variants

Article number	Thread	Exhaust air	Flow rate	Size	Price
139310	G 1/2	G 1/2	4500 l/min	2	94,70 € / Stk
139309	G 3/8	G 1/2	4500 l/min	2	94,70 € / Stk
156616	G 1/4	G 1/4	2000 l/min	1	64,60 € / Stk
156619	G 1	G 1/2	12500 l/min	4	175,40 € / Stk
156617	G 3/8	G 1/4	2000 l/min	1	64,60 € / Stk
156618	G 3/4	G 1/2	12500 l/min	4	175,40 € / Stk

## More Pictures

