


Datasheet for: 102294



Glycerine pressure gauge, triangle front ring, G 1/2, - 1.6 bar

Glycerine pressure gauge, bracket fastening, triangle front ring, Connection, rear, eccentric, G 1/2, Meas. range 0-1.6 bar, Ø100 . Bourdon-tube pressure gauge in standard design, with clamp fixing. For measurements in areas with high, dynamic pressure loads and vibration levels. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	1022
Article number	102294
EAN/barcode	 4047322012201
Your price	135,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.0
Connection	G 1/2
Connection position	rear, excentrical
Diameter	100 mm
Front glass	Plexiglass
Housing	Hot-pressed brass
Lower / Upper range limit	Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	1.6
Measuring range min. bar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK212
Scale graduation in the bar area	0.05 bar
Type	213.40

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
102294	1.0	0.0	1.6	100 mm	G 1/2	135,58 € / Stk
102275	1.6	-1.0	0.0	63 mm	G 1/4	42,87 € / Stk
102276	1.6	-1.0	1.5	63 mm	G 1/4	42,87 € / Stk
102277	1.6	-1.0	3.0	63 mm	G 1/4	42,87 € / Stk
102278	1.6	-1.0	5.0	63 mm	G 1/4	42,87 € / Stk
102279	1.6	0.0	1.6	63 mm	G 1/4	42,87 € / Stk
102280	1.6	0.0	2.5	63 mm	G 1/4	42,87 € / Stk
102281	1.6	0.0	4.0	63 mm	G 1/4	42,87 € / Stk
102282	1.6	0.0	6.0	63 mm	G 1/4	42,87 € / Stk
102283	1.6	0.0	10.0	63 mm	G 1/4	42,87 € / Stk
102284	1.6	0.0	16.0	63 mm	G 1/4	42,87 € / Stk
102285	1.6	0.0	25.0	63 mm	G 1/4	42,87 € / Stk
102286	1.6	0.0	40.0	63 mm	G 1/4	42,87 € / Stk
102287	1.6	0.0	60.0	63 mm	G 1/4	42,87 € / Stk
102288	1.6	0.0	100.0	63 mm	G 1/4	42,87 € / Stk
102289	1.6	0.0	160.0	63 mm	G 1/4	42,87 € / Stk
102290	1.6	0.0	250.0	63 mm	G 1/4	42,87 € / Stk
102291	1.6	0.0	400.0	63 mm	G 1/4	42,87 € / Stk
102292	1.6	0.0	600.0	63 mm	G 1/4	42,87 € / Stk
102293	1.0	-1.0	0.0	100 mm	G 1/2	135,58 € / Stk
102295	1.0	0.0	2.5	100 mm	G 1/2	135,58 € / Stk
102296	1.0	0.0	4.0	100 mm	G 1/2	135,58 € / Stk
102297	1.0	0.0	6.0	100 mm	G 1/2	135,58 € / Stk
102298	1.0	0.0	10.0	100 mm	G 1/2	135,58 € / Stk
102299	1.0	0.0	16.0	100 mm	G 1/2	135,58 € / Stk
102300	1.0	0.0	25.0	100 mm	G 1/2	135,58 € / Stk
102301	1.0	0.0	40.0	100 mm	G 1/2	135,58 € / Stk
102302	1.0	0.0	60.0	100 mm	G 1/2	154,46 € / Stk
102303	1.0	0.0	100.0	100 mm	G 1/2	154,46 € / Stk
102304	1.0	0.0	160.0	100 mm	G 1/2	154,46 € / Stk
102305	1.0	0.0	250.0	100 mm	G 1/2	154,46 € / Stk

Variants

Article number	Accuracy class	Measuring range min. bar	Measuring range max. bar	Diameter	Connection	Price
102306	1.0	0.0	400.0	100 mm	G 1/2	154,46 € / Stk
102307	1.0	0.0	600.0	100 mm	G 1/2	154,46 € / Stk