


Datasheet for: 102126


Glycerine pressure gauge, radial bottom, G 1/2, -1/+1.5 bar, Ø100

Glycerine pressure gauge, CrNi steel housi., Connection radial bottom, G 1/2, Goods class 1.0, Measurement range -1/+1.5 bar, Ø100 . Glycerine-filled bourdon-tube pressure gauge. For measurements in areas with high, dynamic pressure loads and vibration levels. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	720/1-C
Article number	102126
EAN/barcode	 4047322378413
Your price	109,85 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.0
Connection	G 1/2
Connection position	radial on bottom
Crimped bezel	CrNi steel, with glossy metal surface (3-hole bezel)
Diameter	100 mm
Front glass	Transparent plastic
Housing	CrNi steel, with bare metal surface
Lower / Upper range limit	Vacuum/Positive pressure
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Copper alloy
Measuring range max. bar	1.5
Measuring range min. bar	-1.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK208
Scale graduation in the bar area	0.02 bar

Type

213.53

Variants

<i>Article number</i>	<i>Accuracy class</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Diameter</i>	<i>Connection</i>	<i>Price</i>
102126	1.0	-1.0	1.5	100 mm	G 1/2	109,85 € / Stk
102108	1.6	-1.0	0.0	63 mm	G 1/4	27,73 € / Stk
102109	1.6	0.0	1.0	63 mm	G 1/4	27,73 € / Stk
102110	1.6	0.0	1.6	63 mm	G 1/4	27,73 € / Stk
102111	1.6	0.0	2.5	63 mm	G 1/4	27,73 € / Stk
102112	1.6	0.0	4.0	63 mm	G 1/4	27,73 € / Stk
102113	1.6	0.0	6.0	63 mm	G 1/4	27,73 € / Stk
102114	1.6	0.0	10.0	63 mm	G 1/4	27,73 € / Stk
102115	1.6	0.0	16.0	63 mm	G 1/4	27,73 € / Stk
102116	1.6	0.0	25.0	63 mm	G 1/4	27,73 € / Stk
102117	1.6	0.0	40.0	63 mm	G 1/4	27,73 € / Stk
102118	1.6	0.0	60.0	63 mm	G 1/4	27,73 € / Stk
102119	1.6	0.0	100.0	63 mm	G 1/4	27,73 € / Stk
102120	1.6	0.0	160.0	63 mm	G 1/4	27,73 € / Stk
102121	1.6	0.0	250.0	63 mm	G 1/4	27,73 € / Stk
102123	1.6	0.0	400.0	63 mm	G 1/4	27,73 € / Stk
102124	1.6	0.0	600.0	63 mm	G 1/4	27,73 € / Stk
102125	1.0	-1.0	0.0	100 mm	G 1/2	109,85 € / Stk
102128	1.0	0.0	1.0	100 mm	G 1/2	109,85 € / Stk
102129	1.0	0.0	1.6	100 mm	G 1/2	109,85 € / Stk
102130	1.0	0.0	2.5	100 mm	G 1/2	109,85 € / Stk
102131	1.0	0.0	4.0	100 mm	G 1/2	109,85 € / Stk
102132	1.0	0.0	6.0	100 mm	G 1/2	109,85 € / Stk
102133	1.0	0.0	10.0	100 mm	G 1/2	109,85 € / Stk
102134	1.0	0.0	16.0	100 mm	G 1/2	109,85 € / Stk
102135	1.0	0.0	25.0	100 mm	G 1/2	109,85 € / Stk
102136	1.0	0.0	40.0	100 mm	G 1/2	109,85 € / Stk
102137	1.0	0.0	60.0	100 mm	G 1/2	123,94 € / Stk
102138	1.0	0.0	100.0	100 mm	G 1/2	123,94 € / Stk
102139	1.0	0.0	160.0	100 mm	G 1/2	123,94 € / Stk

Variants

<i>Article number</i>	<i>Accuracy class</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Diameter</i>	<i>Connection</i>	<i>Price</i>
102140	1.0	0.0	250.0	100 mm	G 1/2	123,94 € / Stk
102141	1.0	0.0	400.0	100 mm	G 1/2	123,94 € / Stk
102142	1.0	0.0	600.0	100 mm	G 1/2	123,94 € / Stk
102127	1.0	-1.0	3.0	100 mm	G 1/2	109,85 € / Stk
102122	1.6	0.0	315.0	63 mm	G 1/4	27,73 € / Stk