


Datasheet for: 125339


Mist oiler »variobloc« with metal container, Size 2, G 1

Mist oiler »variobloc« with metal container incl. viewing tube, Size 2, G 1, Input pressure max. 20 bar, Medium temp. max. 50 °C . Proportional lubricators, oil can be filled under pressure. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VN 26 M
Article number	125339
EAN/barcode	 4047322212748
Your price	130,70 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	124.0 mm
B	224.0 mm
Bowl	Metal container with viewing tube
C	65.0 mm
Flow rate	7500 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	80 °C
Max. input pressure	20 bar
Max. medium temperature	50 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	WEB
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
125339	G 1	7500 l/min	2	130,70 € / Stk
125335	G 1/4	3400 l/min	1	71,41 € / Stk
125336	G 3/8	4400 l/min	1	71,41 € / Stk
125337	G 1/2	4600 l/min	2	96,33 € / Stk
125338	G 3/4	7500 l/min	2	96,33 € / Stk

More Pictures

