


Datasheet for: 103373


3-way ball valve, T-hole, Lightweight design, Rp 1 1/2

3-way ball valve, T-hole, Lightweight design, nickel-plated brass, Medium/ambient temp. -15 °C to 100 °C, Rp 1 1/2, PN max. 16 bar . Sealing on all sides with T-bore. The lever of this model can only be turned 90° rather than 360°. Only two valve positions are therefore possible instead of four.

Type number	1084 GL
Article number	103373
EAN/barcode	 4047322275866
Your price	137,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	195.0 mm
B	125.0 mm
Ball	Nickel-plated brass
Bore inball	35
DN	40.0
Hand lever	Aluminium, painted black
Housing	Nickel-plated brass
L	147.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure at 20 °C	16 bar
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Page No.	HK293
Sealant	PTFE
Spring	Stainless steel
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 1 1/2
Thread material	Nickel-plated brass

Variants

Article number	Thread	DN	Bore inball	Max. operating pressure at 20 °C	Price
103373	Rp 1 1/2	40.0	35	16 bar	137,34 € / Stk
103372	Rp 1 1/4	32.0	29	16 bar	101,92 € / Stk
103369	Rp 1/2	15.0	13	40 bar	39,03 € / Stk
103374	Rp 2	50.0	44	16 bar	184,63 € / Stk
103370	Rp 3/4	20.0	18	40 bar	50,55 € / Stk
103371	Rp 1	25.0	23	25 bar	69,89 € / Stk

More Pictures

