


Datasheet for: 106675


Valve disc HDM Connection 4mm 2x3/2 NO mono or 5/3 centre aerated

Valve disc for valve terminal HDM, Connect. 4 mm, 2x 3/2-way, NO, monostable or 5/3-way, Centre aerated. These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

Type number	W 4
Article number	106675
EAN/barcode	 4047322286565
Your price	137,74 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Flow rate	200 NI/min
Function	2 x 3/2-way, NO, monostable or 5/3-way, mid-position presurised latching
Manual control	
Max. temperature range	60 °C
Min. temperature range	-10 °C
Page No.	HK483
Piloting	Max. 16 (e.g. 16 spring return valves)
Power input	0.6 W per pilot
Protection IP	IP 65

Variants

Article number	Function	Price
106675	2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised	137,74 € / Stk
106679	5/2-way, bistable (pulse valve)	133,84 € / Stk
106680	5/3-way, mid-position closed	136,21 € / Stk
106674	2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted	132,56 € / Stk
106678	5/2-way, monostable (uses only one pin, two signals assigned)	97,99 € / Stk
106676	3/2-way, NC, monostable and 3/2-way, NO, monostable	137,74 € / Stk
106677	5/2-way, monostable	97,04 € / Stk